



SINCE 1974

Flameproof & Weatherproof Hooter/speaker

● Technical Data : MCH 6001

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1 & IS/IEC 60079-0

PROTECTION :

IP-65 AS PER IS/IEC 60529

AREA CLASSIFICATION :

ZONE-1 & 2

CERTIFICATION :

CIMFR/TC/SR/H413

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINUM ALLOY

RATING :

IN PUT VOLTAGE : Max. UPTO 230 Volts AC.
OR UPTO 110V, DC. / 24V, DC.

IN PUT POWER : UPTO 25 W RMS
AND Max. 38 W.

IMPEDANCE/POWER : 400 Ω /25 W

TAP ON 100V LINE : 500 Ω /20 W

670 Ω /15 W

1K Ω /10 W

2K Ω /05 W

FREQUENCY RESPONSE : 250 - 10 khz

SPL AT 1 khz : 122 db / 25W / 1m

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632 AS PER IS:5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

