



SINCE 1974

Flameproof & Weatherproof Flush Mounting Start-stop Push Button

● Technical Data : PB 61202

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1

PROTECTION :

IP-65 AS PER IS/IEC 60529

AREA CLASSIFICATION :

ZONE -1 & 2

CERTIFICATION :

CIMFR/TC/SR/1268

CIMFR/TC/S/H136

MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST ALUMINIUM ALLOY

RATING & SURFACE TEMP. CLASS :

10A, 550V, AC, 50/60 Hz & T6

COMPONENTS :

A) CONTACT ELEMENT 10A, 500V AC

B) STOP PUSH BUTTON RED SHROUDED WITH "1NC"

CONTACT - 01 No

C) START PUSH BUTTON GREEN SHROUDED WITH "1NO"

CONTACT - 01 No

D) 4 WAY TERMINAL BLOCK - 1 No.

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632 AS PER IS:5

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

1) CABLE GLAND & STOPPER

2) PAINT SHADE AS PER CUSTOMER REQUIREMENT



CUT OUT SIZE
405 x 185 ±3mm

