



SINCE 1974

# Flameproof & Weatherproof Flush Mounting Rotary/Selector Switch

## ● Technical Data : PB61207

### ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1

### PROTECTION :

IP-65 AS PER IS/IEC 60529

### AREA CLASSIFICATION :

ZONE -1 & 2

### CERTIFICATION :

CIMFR/TC/SR/1268

CIMFR/TC/S/H136

### MATERIAL OF CONSTRUCTION :

PRESSURE DIE CAST ALUMINIUM ALLOY

### RATING & SURFACE TEMP. CLASS :

UPTO 32A, 550V, AC, 50/60 Hz & T6

### COMPONENTS :

A) ON-OFF SWITCH, UPTO 32A, 415V AC - 1 No.

B) 4 WAY TERMINAL BLOCK - 1 No.

### FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632 AS PER IS:5

### EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

### CABLE ENTRY :

M20 x 2 Nos.

### OPTIONAL ACCESSORIES AT EXTRA COST :

1) CABLE GLAND & STOPPER

2) PAINT SHADE AS PER CUSTOMER REQUIREMENT



CUT OUT SIZE  
405 x 185 ±3mm

