



SINCE 1974

Flameproof & Weatherproof Integral Bulkhead Fixture

● Technical Data : LB 61125

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1
& IS/IEC 60079-0

PROTECTION :

IP-66 AS PER IS/IEC 60529

AREA CLASSIFICATION :

ZONE-1, 2, 21 & 22

CERTIFICATION :

CIMFR/TC/SR/337

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINUM ALLOY.

RATED VOLTAGE :

240V \pm 10V AC 50/60Hz

VOLTAGE OTHER THEN SPECIFIED IS ON REQUEST

RATING & TEMP. CLASSIFICATION :

80/125WATT HPMV - T4

70WATT MH - T5

70WATT HPSV - T5

2 x 23W CFL - T6

COMPONENTS :

GEAR PLATE WITH FOLLOWING COMPONENTS

A) BALLAST

B) CAPACITOR & (IGNITOR FOR HPSV/MH LAMP)

C) 2 WAY TERMINAL BLOCK

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR FLAT GLASS

LAMP HOLDER :

PORCELAIN E-27

WIRE GUARD :

M.S. GALVANIZED & WHITE EPOXY PAINTED

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632
AS PER IS:5

HWARE ARD:

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST:

1) DOUBLE COMPRESSION CABLE GLAND/STOPPER (BNP/SS)

2) PAINT SHADE AS PER CUSTOMER REQUIREMENTS.

3) LAMP

SPECIAL FEATURES :

A) SUPERIOR FINISH WITH EPOXY POWDER COATED

B) MIRROR POLISHED INTERNAL REFLECTOR

C) EASY TO REPLACE THE LAMP

