



SINCE 1974

Flameproof & Weatherproof Emergency Tube Light Fixture

● Technical Data : FLT 61...Series

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1 &
IS/IEC 60079-0

PROTECTION :

IP-66 AS PER IS/IEC 60529:2001

AREA CLASSIFICATION :

ZONE-1, 2, 21 & 22

CERTIFICATION :

CIMFR/TC/SR/96

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINUM ALLOY

RATED VOLTAGE :

240V \pm 10V AC 50/60Hz
VOLTAGE OTHER THEN SPECIFIED IS ON REQUEST

RATING & TEMP. CLASSIFICATION :

11 WATT COMPACT FLUORESCENT TUBE LAMP - T6
8 WATT FLUORESCENT TUBE LAMP - T6

TRANSPARENT PART :

HEAT RESISTANT & BOROSILICATED CLEAR TUBULAR GLASS

BATTERY BACK-UP :

Ni-cd. RECHARGEABLE BATTERY

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632
AS PER IS:5

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST:

- 1) MOUNTING BRACKET AS PER CUSTOMER REQUIREMENT
- 2) PAINT SHADE AS PER CUSTOMER REQUIREMENTS.
- 3) DOUBLE COMPRESSION CABLE GLAND/STOPPER (BNP/SS)
- 4) LAMP

SPECIAL FEATURES :

- A) SUPERIOR FINISH WITH EPOXY POWDER COATED
- B) EASY TO REPLACE THE LAMP

