



SINCE 1974

Flameproof & Weatherproof Hand Lamp Fitting

● Technical Data : LH 61060

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1
& IS/IEC 60079-0

PROTECTION :

IP-66 AS PER IS/IEC 60529

AREA CLASSIFICATION :

ZONE-1, 2, 21 & 22

CERTIFICATION :

CIMFR/TC/SR/1584
CIMFR/TC/SR/819

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINUM ALLOY

RATED VOLTAGE :

240V \pm 10V AC 50/60Hz
VOLTAGE OTHER THEN SPECIFIED IS ON REQUEST

RATING & TEMP. CLASSIFICATION :

60 Watt GLS LAMP - T6
100 Watt GLS LAMP - T6

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR DOME GLASS

LAMP HOLDER :

PORCELAIN E-27

WIRE GUARD :

M.S GALVANIZED & WHITE EPOXY PAINTED

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 1 No. OUTSIDE

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632
AS PER IS:5

CABLE ENTRY :

M20 x 1 No.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) DOUBLE COMPRESSION CABLE GLAND (BNP/SS)
- 2) PAINT SHADE AS PER CUSTOMER REQUIREMENT
- 3) LAMP

SPECIAL FEATURES :

- A) SUPERIOR FINISH WITH EPOXY POWDER COATED
- B) EASY TO REPLACE THE LAMP

NOTE:

- 1) MOC: STAINLESS STEEL / CAST IRON ON REQUEST

