



SINCE 1974

Flameproof & Weatherproof Reaction Vessel Lamp

● Technical Data : RV 61100

ENCLOSURE :

Ex-d, GAS Gr. IIA, IIB & IIC AS PER IS/IEC 60079-1 & IS/IEC 60079-0

PROTECTION :

IP-66 AS PER IS/IEC 60529

AREA CLASSIFICATION :

ZONE-1, 2, 21 & 22

CERTIFICATION :

CIMFR/TC/SR/1572

MATERIAL OF CONSTRUCTION :

DIE CAST ALUMINUM ALLOY.

RATED VOLTAGE :

240V \pm 10V AC 50/60Hz

VOLTAGE OTHER THEN SPECIFIED IS ON REQUEST

RATING & TEMP. CLASSIFICATION :

60 Watt GLS LAMP - T5

18/20 Watt CFL LAMP - T6

100 Watt GLS LAMP - T5

TRANSPARENT PART :

HEAT RESISTANT & TOUGHENED CLEAR FLAT GLASS

LAMP HOLDER :

PORCELAIN E-27

SWITCH :

16A, DP, ON-OFF, 250V, A.C. 50Hz

FINISH :

DARK ADMIRALTY GREY EPOXY POWDER COATED SHADE 632 AS PER IS:5

HARDWARE :

STAINLESS STEEL

EARTHING :

1 No. INSIDE & 2 Nos. OUTSIDE

CABLE ENTRY :

M20 x 2 Nos.

OPTIONAL ACCESSORIES AT EXTRA COST :

- 1) DOUBLE COMPRESSION CABLE GLAND/STOPPER (BNP/SS)
- 2) PAINT SHADE AS PER CUSTOMER REQUIREMENT.
- 3) LAMP
- 4) WITH TIMER & PUSH BUTTON

SPECIAL FEATURES :

- A) SUPERIOR FINISH WITH EPOXY POWDER COATED
- B) EASY TO REPLACE THE LAMP

