



WE RESERVE THE RIGHTS AT ANY TIME TO MAKE ANY SPECIFICATION OR DIMENSIONAL CHANGES DEEMED NECESSARY TO ENSURE ADVANCEMENT IN THE DESIGN OR MANUFACTURE OF ANY PRODUCT

MM ²	E Bolt MMø	øA	øC	D	F	B	K	G-H	J	Dowell's CAT. No.	SYB 95	SYD 20A	SYE 150A	SYT-7	SYT -102 R	STD PKG
2.5	M3	2.0	5.5	7.0	3.5	7	3	8	18	ALS-151						200
	M3.5	2.6			2.9					ALS-309	SYT -17					
4.0	M4	2.9	5.5	7.0	2.6	7	3	8	18	ALS-155						200
	M5			12.0	1.2	7	4	13	24	ALS-317	SYA - 427		SYB - 95			
6.0	M5			8.0	2.0					ALS-158						200
	M6	3.5	5.5	12.0	1.1	7	4	13	24	ALS-313	SYT - 2			SYT 102		
10	M6			10.0	2.8					ALS-214						200
	M8	4.4	7.4	15.0	1.8	9	4	17	30	ALS-215	JBR-1					
16	M6			11.0	2.9					ALS-252						200
	M8	5.4	8.3	11.0	2.9	13	4	20	37	ALS-216	JBR-2					
25	M8			14.0	3.0					ALS-218						100
	M10	7.0	10.0	20.0	1.7	16	7	21	44	ALS-219	JBR-4					
35	M8			15.0	2.8					ALS-221						100
	M10	8.0	10.8	20.0	2.1	18	7	22	47	ALS-222	JBR-5					
50	M8			18.0	3.7					ALS-255						100
	M10	9.3	13.0	23.0	2.8	22	8	24	54	ALS-312	JBR-7			HY-267		
70	M8			23.0	2.8					ALS-224						50
	M10	11.6	16.0	22.0	4.4	26	8	26	60	ALS-256	JBR-9			HY-268		
95	M12	12.9	17.1	25.0	4.2	28	8	28	64	ALS-225						50
	M16									ALS-226	JBR-10			HY-269		
120	M10									ALS-227						30
	M12	14.8	19.6	28.0	4.8	32	11	30	73	ALS-230	JBR-11	JDR-11	JER-11	JEK-402	HY-270	
150	M12									ALS-231						20
	M16	16.1	21.2	31.0	5.1	34	11	34	79	ALS-258		JDR-12	JER-12	JEK- 403	HY-271	
185	M10									ALS-232						10
	M12	18.0	23.7	34.0	5.7	36	12	36	84	ALS-233		JDR-13	JER-13	JEK-404	HY-272	
225	M12	20.6	27.0	39.0	6.4	40	14	40	94	ALS-311						10
	M16									ALS-234		JDR-13	JER-14	JEK-405	HY-273	
240	M12	22.0	28.0	40.0	6.0	44	14	44	102	ALS-235						10
	M16									ALS-236		JDR-14	JER-15	JEK-406	HY-273	
300	M16	24.0	31.0	45.7	7.0	47	14	54	115	ALS-237						10
	M20									ALS-300		JDR-150	JER-16	JEK-407	HY-274	
400	M20	28.0	36.0	51.0	8.0	56	13	61	130	ALS-259						5
	M20	30.0	41.0	58.0	11.0	60	15	65	140	ALS-260			JER-18	JEK-277	HY-275	
500	M20	35.0	46.0	66.0	11.0	69	16	69	154	ALS-296			JER-20		HY-279	5
	M20	39.0	51.0	73.0	12.0	77	25	78	180	ALS-261			JER-21		HY-280	
800	M20									ALS-261			JER-27			5
	M20	43.5	57.0	81.0	13.5	100	30	90	220	ALS-318			JER-29			
1000										ALS-319						4

MATERIAL-ELECTROLYTIC ALUMINIUM IS 5082/IS 8309

TOLERANCE=± 5%

FINISH : NATURAL