



mm ²	Ø A	Ø C	Ø D	D-1	B	K	G+H	J	Dowell's Cat No.	RECOMMENDED TOOLS & DIES						STD PKG					
										SYB 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R						
2.5	2.0	5.5	4.5	4.0	7	4	10	21	AWP-1 AWP-7	SYT -17	SYA - 427	SYT - 2	SYB - 95	SYT 102 R	200						
	2.6		3.8	3.3		4	10														
4.0	2.9	5.5	4.5	4.0	7	4	10	21	AWP-15 AWP-16	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R						
			3.8	3.3		4	10														
6.0	3.5	5.5	4.5	4.0	7	4	10	21	AWP-17 AWP-18	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R						
			3.8	3.3		4	10														
10	3.8	7.4	4.5	4.0	9	4	10	23	AWP-19 AWP-20 AWP-21 AWP-22	JBR-1	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			3.8	3.3		9	4										10	23			
			4.4	4.0		9	4										10	23			
			4.4	3.8		9	4										10	23			
16	5.4	8.3	6.0	5.5	13	5	15	33	AWP-23 AWP-24 AWP-2	JBR-2	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			5.5	13		5	20										38	16	200		
			3.8	3.3		13	5										13	31			
25	7.0	10.0	6.0	5.5	16	5	15	36	AWP-25 AWP-3	JBR-4	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			7.5	6.5		16	5										20	41	25	100	
35	8.0	10.8	7.5	6.5	18	5	20	43	AWP-4 AWP-26 AWP-5	JBR-5 JBR-7	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			6.5	22		5	20										47	35	100		
50	9.3	13.0	7.5	6.5	22	5	20	47	AWP-27 AWP-6 AWP-28 AWP-29	JBR-9	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			14	13		22	7										24	53	50	HY-267	100
70	11.6	16.0	7.5	6.5	26	5	20	51	AWP-7 AWP-8 AWP-31 AWP-32	JBR-10	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			11.5	10.5		5	32										63	56	50	HY-268	50
			11.5	10.5		6	25										59	61	50	HY-269	50
			7.5	6.5		6	22										56	66	50	HY-269	50
95	12.9	17.1	15.6	14.0	28	6	27	61	AWP-33 AWP-34 AWP-35 AWP-36	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			12.8	11.8		6	32										66	61	30	HY-270	30
			11.5	10.5		6	25										63	60	30	HY-270	30
			7.5	6.5		6	22										60	70	30	HY-270	30
120	14.8	19.6	11.5	10.5	32	6	32	70	AWP-37 AWP-10 AWP-37	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			15.6	14		6	32										70	70	20	HY-271	20
			15.6	14		6	32										72	74	20	HY-271	20
150	16.1	21.2	15.6	14	34	6	32	72	AWP-30 AWP-38	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			11.5	10.5		6	32										74	74	10	HY-272	10
185	18.0	23.7	15.6	14	36	6	32	74	AWP-39 AWP-46 AWP-42	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			11.5	10.5		6	32										80	80	10	HY-273	10
225	20.6	27.0	21	18	40	8	42	90	AWP-44 AWP-43	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			16	15		8	42										90	94	10	HY-273	10
240	22.0	28.0	16	15	44	8	42	94	AWP-45 AWP-47	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			15.6	14		8	32										84	84	10	HY-273	10
300	24.0	31.0	16	15	47	8	42	97	AWP-45 AWP-47	JBR-11	SYB - 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R					
			15.6	14		8	32										87	87	10	HY-274	10

MATERIAL-ELECTROLYTIC ALUMINIUM IS 5082

TOLERANCE=± 5%

FINISH : NATURAL