



| Sr. No. | Dowell's Cat. No. | Size (Sq-mm) | E | DIA A | B | F | D | J |
|---------|-------------------|--------------|------|-------|----|------|-----|-----|
| 1 | CAF 25-10 | 25 | 10.5 | 7.5 | 30 | 4 | 19 | 70 |
| 2 | CAF 35-10 | 35 | 10.5 | 8.5 | 30 | 4 | 19 | 70 |
| 3 | CAF 50-13 | 50 | 13 | 10.2 | 35 | 5 | 24 | 85 |
| 4 | CAF 70-13 | 70 | 13 | 11.5 | 45 | 5 | 24 | 90 |
| 5 | CAF 95-13 | 95 | 13 | 13.5 | 50 | 5 | 24 | 95 |
| 6 | CAF 120-13 | 120 | 13 | 15.5 | 55 | 6 | 30 | 105 |
| 7 | CAF 150-13 | 150 | 13 | 16.5 | 60 | 6 | 30 | 110 |
| 8 | CAF 185-13 | 185 | 13 | 18 | 60 | 7 | 35 | 130 |
| 9 | CAF 240-13 | 240 | 13 | 22 | 65 | 7 | 35 | 135 |
| 10 | CAF 300-17 | 300 | 17 | 23.5 | 70 | 7.5 | 36 | 140 |
| 11 | CAF 400-17 | 400 | 17 | 26.5 | 75 | 7.5 | 36 | 145 |
| 12 | CAF 500 | 500 | - | 30 | 95 | 10.5 | 50 | 200 |
| 13 | CAF 630 | 630 | - | 34 | 95 | 10.5 | 60# | 200 |

Note :-

*All Dimensions are in mm

*Raw Materials : (Copper : E. C. Grade as per IS-191)
(Aluminium : E. C. Grade as per IS - 5082)

*Tolerances : +/- 5%

*Joining Method : Friction Welding

*# Square Palm of Given Dimension with as per Required E Hole

*Recommended Crimping Tool SYE -150 B