


# COPPER TUBULAR TERMINAL ENDS FOR SOLDERLESS CRIMPING TO COPPER CONDUCTORS

REF : D.L.W.

mm <sup>2</sup>	'C' Cable Size	mm <sup>2</sup>	'C-1' Cable Size	A	C	J	Dowell's Cat No.	Retail Packing	Recommendation		
									Crimping Tool	Forming Die	Crimping Die
1.5	1/1.4	1.5	1/1.4	1.6	3.2	15	EH-453	200	A	-	-
2.5	1/1.8	2.5	1/1.8	2.0	3.7	15	CB-23	200	A	-	-
4	1/2.8	4	1/2.8	3.1	4.8	15	CB-3	200	A	-	-
6	1/3.55	6	1/3.55	3.8	5.5	15	CB-4	200	A	-	-
10	7/1.4	10	7/1.4	4.4	6.2	20	EH-460	200	B,D	-	R-1
16	7/1.7	16	7/1.7	5.3	7.1	20	CB-6	200	B,D	-	R-2
25	7/2.24	25	7/2.24	7.0	9.0	25	CB-7	200	B,D	F-25	R-3
35	7/2.5	35	7/2.5	8.0	10.0	30	CB-8	100	B,D	F-35	R-4
50	19/1.8	50	19/1.8	9.2	11.2	35	CB-9	100	B,D,E	F-50	R-6
70	19/2.24	70	19/2.24	11.5	13.8	40	CB-10	50	B,D,E	F-70	R-7
95	19/2.5	95	19/2.5	12.8	15.6	45	CB-11	50	B,D,E	F-95	R-9
120	37/2.06	120	37/2.06	14.8	17.8	50	CB-12	30	B,D,E	F-120	R-10
150	37/2.24	150	37/2.24	16.0	19.6	55	CB-13	20	D,E	F-150	R-11
185	37/2.5	185	37/2.5	18	22	60	CB-14	20	D,E	F-185	R-12
225	37/2.8	225	37/2.8	20	24	65	CB-20	10	D,E	F-225	R-13
240	61/2.24	240	61/2.24	22	26	65	CB-15	10	D,E	F-240	R-14
300	61/2.5	300	61/2.5	24	28.7	75	CB-16	10	D,E	F-300	R-15
400	61/3.00	400	61/3.00	28	33.2	90	CB-17	5	D,E	F-400	R-17
500	91/2.65	500	91/2.65	30	36	95	CB-18	5	E	F-500	R-18
625	91/3.0	625	91/3.0	35	41.5	105	CB-19	5	E	F-625	R-19
800	91/3.35	800	91/3.35	39	46.3	120	CB-21	5	E	-	R-23
1000	91/3.65	1000	91/3.65	43	53.8	150	CB-22	4	E	-	R-22



**MATERIAL - COPPER IS : 191**  
**Finish - Electro Tinned**

Crimping tool abbreviation  
A = KOP E=SYE 150A  
B=BRD D=SYD 20A