



SYT - 7



SYT - 9

SYE - 150

WE RESERVE THE RIGHTS AT ANY TIME TO MAKE ANY SPECIFICATION OR DIMENSIONAL CHANGES DEEMED NECESSARY TO ENSURE ADVANCEMENT IN THE DESIGN OR MANUFACTURE OF ANY PRODUCT

MM ²	E Bolt MMØ	øA	øC	D	F	B	K	G-H	J	Dowell's CAT. No.	SYB 95	SYD 20A	SYE 150A	SYT 7	SYT 9	SYT-102 R	STD PKG
2.5	M3	2.0	5.5	7.0	3.5	10.5	3	8	21.5	ALS-551	SYT -17	SYB - 95	SYT 7	SYT 9	SYT-102 R	200	
	M3.5	2.6	5.5	7.0	2.9												ALS-509
4.0	M4	2.9	5.5	7.0	2.6	10.5	3	8	21.5	ALS-555	SYA - 427	SYB - 95	SYT 7	SYT 9	SYT-102 R	200	
	M5	12.0	1.2	8.0	2.0												ALS-517
6.0	M5	3.5	5.5	12.0	1.1	10.5	4	13	27.5	ALS-558	SYT - 2	SYB - 95	SYT 7	SYT 9	SYT-102 R	200	
	M6	12.0	1.1	10.0	2.8												ALS-513
10	M6	4.4	7.4	10.0	1.8	13.5	4	17	34.5	ALS-514	JBR-1	SYB - 95	SYT 7	SYT 9	SYT-102 R	200	
	M8	15.0	1.8	11.0	2.9												ALS-515
16	M6	5.4	8.3	11.0	2.9	19.5	4	20	43.5	ALS-516	JBR-2	SYB - 95	SYT 7	SYT 9	SYT-102 R	200	
	M10	18.0	1.8	14.0	3.0												ALS-617
25	M8	7.0	10.0	20.0	1.7	24	7	21	52	ALS-518	JBR-4	SYB - 95	SYT 7	SYT 9	SYT-102 R	100	
	M12	20.0	1.7	18.0	1.8												ALS-519
35	M8	8.0	10.8	15.0	2.8	27	7	22	56	ALS-520	JBR-5	SYB - 95	SYT 7	SYT 9	SYT-102 R	100	
	M10	20.0	2.1	18.0	3.7												ALS-521
50	M8	9.3	13.0	23.0	2.8	33	8	24	65	ALS-522	JBR-7	SYB - 95	SYT 7	SYT 9	SYT-102 R	100	
	M12	23.0	2.8	18.0	3.7												ALS-655
70	M10	11.6	16.0	22.0	4.4	39	8	26	73	ALS-512	JBR-9	SYB - 95	SYT 7	SYT 9	SYT-102 R	50	
	M12	23.0	2.8	18.0	3.7												ALS-524
95	M10	12.9	17.1	25.0	4.2	42	8	28	78	ALS-525	JBR-10	SYB - 95	SYT 7	SYT 9	SYT-102 R	50	
	M16	23.0	2.8	18.0	3.7												ALS-526
120	M10	14.8	19.6	28.0	4.8	48	11	30	89	ALS-527	JBR-11	SYB - 95	SYT 7	SYT 9	SYT-102 R	30	
	M12	23.0	2.8	18.0	3.7												ALS-528
150	M12	16.1	21.2	31.0	5.1	51	11	34	96	ALS-529	JBR-12	SYB - 95	SYT 7	SYT 9	SYT-102 R	20	
	M16	23.0	2.8	18.0	3.7												ALS-529
185	M10	18.0	23.7	34.0	5.7	54	12	36	102	ALS-557	JBR-13	SYB - 95	SYT 7	SYT 9	SYT-102 R	10	
	M12	23.0	2.8	18.0	3.7												ALS-530
225	M12	20.6	27.0	39.0	6.4	60	14	40	114	ALS-531	JBR-14	SYB - 95	SYT 7	SYT 9	SYT-102 R	10	
	M16	23.0	2.8	18.0	3.7												ALS-531
240	M10	22.0	28.0	40.0	6.0	66	14	44	124	ALS-532	JBR-15	SYB - 95	SYT 7	SYT 9	SYT-102 R	10	
	M16	23.0	2.8	18.0	3.7												ALS-532
300	M16	24.0	31.0	45.7	7.0	70.5	14	54	138.5	ALS-533	JBR-16	SYB - 95	SYT 7	SYT 9	SYT-102 R	10	
	M20	23.0	2.8	18.0	3.7												ALS-533
400	M16	28.0	36.0	51.0	8.0	84	13	61	158	ALS-511	JBR-18	SYB - 95	SYT 7	SYT 9	SYT-102 R	5	
	M20	23.0	2.8	18.0	3.7												ALS-534
500	M20	30.0	41.0	58.0	11.0	90	15	65	170	ALS-535	JBR-20	SYB - 95	SYT 7	SYT 9	SYT-102 R	5	
	M10	23.0	2.8	18.0	3.7												ALS-511
630	M20	35.0	46.0	66.0	11.0	103.5	16	69	188.5	ALS-534	JBR-21	SYB - 95	SYT 7	SYT 9	SYT-102 R	5	
	M16	23.0	2.8	18.0	3.7												ALS-534
800	M20	39.0	51.0	73.0	12.0	115.5	25	78	218.5	ALS-535	JBR-27	SYB - 95	SYT 7	SYT 9	SYT-102 R	5	
	M16	23.0	2.8	18.0	3.7												ALS-535
1000	M20	43.5	57.0	81.0	13.5	150	30	90	270	ALS-500	JBR-29	SYB - 95	SYT 7	SYT 9	SYT-102 R	4	
	M16	23.0	2.8	18.0	3.7												ALS-500

MATERIAL-ELECTROLYTIC ALUMINIUM IS 5082/IS 8309

TOLERANCE=± 5%

FINISH : NATURAL